


Mounted Bearings

Nomenclature



Housing style		Products
F4B / F4S / F4R	4-bolt flange (S=square, R=round)	Ball, roller, plain
FC	Flanged cartridge (piloted)	Ball, roller, plain
HNG	Hanger bearing	Ball, roller, plain
INS	Insert	Ball, roller, plain
NSTU	Narrow-slot take-up	Ball, roller, plain
P2B / P4B	2-bolt pillow block / 4-bolt pillow block	Ball, roller, plain
WSTU	Wide-slot take-up	Ball, roller, plain
F3B / F3R	3-bolt flange (R=round)	Ball, roller
TP / TPHU	Top-angle / Top-angle heavy-duty universal	Ball, roller
CYL	Cylindrical housing unit	Ball, plain
F2B / F2BZ	2-bolt flange (Z=pilot on backside)	Ball, plain
FB	Flange bracket (3-bolt, offset insert)	Ball, plain
LF / LFT	Light-duty flange (LF=3-bolt, LFT=2-bolt)	Ball, plain
F&B	Fan and blower pillow block	Ball
INS-ER	Insert with cylindrical outer diameter (OD)	Ball
SCHB	Screw conveyor hanger bearing	Ball
SO	Stand-off	Ball (FoodSafe™)
TB	Tapped-base pillow block	Ball
B1U	B1 cartridge unit	Roller
CRT	Cartridge unit (all steel)	Roller
DU	D insert unit	Roller
S1U	S1 insert unit	Roller
Prefixes		
S	Steel housing	Roller (spherical)
E	E-dimension housing	Roller
Type		Products
CC	Wide inner ring, normal duty, clamp collar (fan and blower)	Ball
DL	D-Lok, wide inner ring, concentric clamp collar	Ball
DLED	D-Lok Harsh Duty™	Ball
G	Take-up, wide inner ring, clamp collar	Ball
GT	Grip Tight®, adapter	Ball
GTED	Grip Tight Harsh Duty	Ball

Type (continued)		Products
GXR	Take-up, wide inner ring, normal duty, eccentric collar	Ball
GXRED	Eccentric Collar Harsh Duty	Ball
SC	Wide inner ring, normal duty, set screw	Ball
SC3	Wide inner ring, set screw locking, 300-series bearing	Ball
SCED	Set Screw Harsh Duty	Ball
SCFS	FoodSafe	Ball
SL / SLX	Narrow inner ring, light duty, stamped steel housing, set screw / eccentric collar	Ball
SXR	Wide inner ring, normal duty, eccentric collar	Ball
SXV	Narrow inner ring, intermediate duty, eccentric collar	Ball
VSC	Wide inner ring, intermediate duty, set screw locking	Ball
IP / ISAF / ISN	Safety Mount® IP / SAF / SN	Roller (spherical)
S2	S-2000	Roller (spherical)
SAFS	SAF steel housing	Roller (spherical)
SFXT	SAF-XT	Roller (spherical)
SS	Split-Sphere	Roller (spherical)
UN2	Unisphere® II	Roller (spherical)
USAF / USDAF	USAF / USDAF	Roller (spherical)
C	Type C, clamp collar	Roller (tapered)
DI	Double Interlock®	Roller (tapered)
E / EXL	Type E or Type EXL (E-dimensioned with split housing)	Roller (tapered)
ED	Type E Harsh Duty	Roller (tapered)
HC	Hinged cap	Roller (tapered)
K	Type K	Roller (tapered)
SD	Special Duty	Roller (tapered)
TAF	Tapered SAF	Roller (tapered)
TAFD	TAF Harsh Duty	Roller (tapered)
BAA / BAP / BAR	Babbitted angle / plate / rigid	Plain
BASO / BASP	Babbitted solid or split	Plain
BO / BOTU	Bronzoil or Bronzoil take-up	Plain
BZA / BZR / BZSP	Bronze-Bushed angle, rigid, split	Plain
GLT7 / GLT10	Take-up, Solidlube® 700 or 1000 series	Plain
LM8	Solidlube 800 series	Plain
LT7 / LT10	Solidlube 700 or 1000 series	Plain

CONTINUED

Type (continued)		Products
MM7 / MM10	Solidlube MM700 or 1000 series	Plain
PSEZ	Polymer sleeve E-Z Kleen®	Plain
PL / PLWC	Plain or plain water-cooled Sleeveoil®	Plain (hydrodynamic)
PLXC	Plain externally-cooled Sleeveoil	Plain (hydrodynamic)
RTL	Radial thrust-loaded Sleeveoil	Plain (hydrodynamic)
SSH / STD	Short / standard Sleeveoil	Plain (hydrodynamic)
SSL / STL	Short / standard Sleeveoil	Plain (hydrodynamic)
XC	Externally-cooled Sleeveoil	Plain (hydrodynamic)

Suffix

AG	Agriculture Duty (Triple-lip seal with metal shield, Maxlife cage, SHC PM 220 grease 100% full) for SXR and SXRb eccentric collar units
AH	Air handling
B	Low backing height pillow block
EZ	Washdown (E-Z Kleen or Ultra Kleen® ball bearings)
H	High backing height (non-expansion and expansion)
M	Medium duty
U	Higher back pillow block (for interchangeability with competitors)

Shaft size

Inches	1st digit = inches, 2nd and 3rd digits = 1/16-inch increment (108 = 1-1/2")
Metric	2nd and 3rd digits + "M" (50M or 050M)

Modifications or features	Products
MOD	Modified (miscellaneous)
NY	Nylon coated
E	Expansion
NL	No lube (sealed for life)
HT	High temperature option (400 °F maximum)
P	White polymer housing
ABHS	Air baggage handling system
BEV	Beverage industry modifications

Modifications or features (continued)		Products
CR	Corrosion-resistant insert	Ball
FF	ProGuard plus seals (with flingers)	Ball
LL	Low torque labyrinth seal	Ball
RL	Relube (used with SL and SLX flanges)	Ball
SH / SS	Stainless-steel housing or insert	Ball
SHFS	Stainless-steel housing with FoodSafe insert	Ball
L	Labyrinth seal	Roller (S2 and IP spherical, tapered)
R	Rubbing lip seals	Roller
AH	Air handling	Roller (spherical)
FR / FS	Non-expansion (R=rubbing lip seal / S=labyrinth seal)	Roller (spherical, ISN only)
LR / LS	Expansion (R=rubbing lip seal / S=labyrinth seal)	Roller (spherical, ISN only)
AUX	Auxiliary seal	Roller (spherical, SAF only)
LER	Labyrinth seal	Roller (spherical, SAF only)
TT / TTDN	Triple-tect / TT "drop-in" seal	Roller (spherical, SAF only)
WD	Wet-duty seal	Roller (tapered)